



GSP 4

Portable gas sniffer



Management System
ISO 9001:2015





- Fast and reliable detection
- Sensor for a wide range of flammable gases
- Sensor poisoning protection
- Flexible gas probe
- Audible alarm if limit values are exceeded



The portable gas detector GSP 4 serves to sniff out gas leaks of flammable gases in gas pipes, gas meters, gas burners and gas tanks.

Thanks to the flexible gas probe, even difficult to access spaces can be reached easily. The gas detector reacts to all flammable gases such as methane, propane, butane (base calibration: methane) and has integrated a sensor poisoning protection for a long service life.

The intensity of the escaping gas is indicated by the three LEDs. At the same time, the instrument generates an audible signal whose frequency is proportional to the gas concentration. The detector switches off automatically after four minutes.

Technical specifications

Dimensions H x W x D	392 x 45 x 30 mm (incl. sensor)
Weight	approx. 158 g
Measuring range	0 to 2,000 ppm methane CH ₄
Accuracy	± 500 ppm
Detection sensitivity	> 50 ppm
Indication	3 LEDs
Operating temperature	0 to +40 °C
Storage temperature	-20 to +40 °C
Battery type	2x AAA batteries (micro)
Operating time	up to 10 hours



SYSTRONIK

Messtechnologie

Member of AFRISO-EURO-INDEX group

SYSTRONIK Elektronik und Systemtechnik GmbH

Gewerbestraße 57
88636 Illmensee, Germany

Phone +49 7558 9206 - 0
Fax +49 7558 9206 - 20

info@systronik.de
www.systronik.com

Subject to change - v20001

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by SYSTRONIK is under license. Google Play and the Google Play logo are trademarks of Google LLC. Apple and the Apple logo are trademarks of Apple Inc.